

EMPLOYMENT POLICY MANUAL

Subject:	Approval Date:	By-Law No.	
Working Around Water	May 19, 2020	40-2020	

"*" 2019 Occupational Health and Safety Act with Regulations for Ontario – Construction Projects

3.44 WORKING AROUND WATER

1. <u>GENERAL POLICY</u>

1.1 Municipal Policy for working over and around water, including docks which are maintained by the Municipality shall be guided by criteria established by Council.

2. <u>DEFINITIONS</u>

- 2.1 "Employee" shall mean a person who works for the Municipality of Red Lake.
- 2.2 "Municipality" shall mean The Corporation of the Municipality of Red Lake.
- 2.3 "Personal Flotation Device" shall mean a piece of equipment designed to assist a wearer to keep afloat in water. This includes life jacket, life preserver or flotation suit.
- 2.4 "Shore" shall mean solid land adjacent to water.

3. <u>REQUIREMENTS – CONSTRUCTION PROJECTS</u>

- 3.1 All employees working in an area where the water depth is one (1) meter or greater, shall wear a personal flotation device.*
- 3.2 Minimum two (2) workers trained to perform rescue operations (C.P.R) shall be available on site to perform rescue operations.*
- 3.3 One employee shall remain on shore at all times.*
- 3.4 The employee on shore shall have a buoy attached to a buoyant line not less than fifteen (15) meters in length.*
- 3.5 All workers on the project shall be advised of the rescue procedures to be followed and their role, if any, in carrying out a rescue.*
- 3.6 Rescue equipment shall be provided in a suitable location, on or near the work location.*
 - 3.6.1 Rescue equipment shall include:*
 - 3.6.1.1 A Buoy attached to a buoyant line not less than fifteen (15) meters in length and a boat hook;*
 - 3.6.1.2 A whistle (alarm) warning a worker of the necessity to carrying out a rescue operation;*



EMPLOYMENT POLICY MANUAL

Subject:	Approval Date:	By-Law No.	
Working Around Water	May 19, 2020	40-2020	

3.6.1.2.1 A whistle (alarm) shall be worn by an employee on shore; and*

- 3.6.1.3 A seaworthy boat, which shall be power driven.*
- 3.7 A written emergency plan shall be completed prior to working around water and shall include:
 - 3.7.1 Location of the work;
 - 3.7.2 Nature and type of work being completed;
 - 3.7.3 Type of body of water (tides, currents, depth, estimated temperature);
 - 3.7.4 Measurements in place to protect worker from falling;
 - 3.7.5 Number of workers on site;
 - 3.7.6 Work schedule how long will it take to complete;
 - 3.7.7 Weather conditions;
 - 3.7.8 What work platforms will be present (platforms, boats, etc.);
 - 3.7.9 How workers and equipment will be transported to the site; and
 - 3.7.10 Procedure to be followed if a worker has fallen into the water (ex: type of Boat present, equipment needed, first aid procedures)

4. <u>REQUIREMENTS – MINOR REPAIRS</u>

- 4.1 All employees working in an area where the water depth is one (1) meter or greater, shall wear a personal flotation device.*
- 4.2 Minimum two (2) workers trained to perform rescue operations (C.P.R) shall be available on site to perform rescue operations.*
- 4.3 One employee shall remain on shore at all times.*
- 4.4 The employee on shore shall have a buoy attached to a buoyant line not less than fifteen (15) meters in length.*

The Corporation of the Municipality of Red Lake



EMPLOYMENT POLICY MANUAL

Subject:	Approval Date:	By-Law No.	
Working Around Water	May 19, 2020	40-2020	

- 4.5 All workers on performing the task shall be advised of the rescue procedures to be followed and their role, if any, in carrying out a rescue.*
- 4.6 Rescue equipment shall be provided in a suitable location, on or near the work location.*
 - 4.6.1 Rescue equipment shall include:*
 - 4.6.1.1 A Buoy attached to a buoyant line not less than fifteen (15) meters in length and a boat hook.*
 - 4.6.1.1.1 The employee on shore shall have the buoy and buoyant line with them at all times.*
 - 4.6.2.1 A whistle (alarm) warning a worker of the necessity to carrying out a rescue operation.*
 - 4.6.2.1.1 A whistle (alarm) shall be worn by an employee on shore.*
- 4.7 A written emergency plan shall be completed prior to working around water and shall include all items listed in Section 3.7.

5. <u>LADDERS</u>

- 5.1 A fixed ladder shall be provided at the dock which shall;
 - 5.1.1 Comply with O. Reg. 312/91, section 84;*
 - 5.1.2 be vertical in length;
 - 5.1.3 Have rest platforms at not more than nine (9) meter intervals;
 - 5.1.4 Have side rails that extend ninety (90) centimeters above the landing;
 - 5.1.5 Have an adequate landing surface that is clear of obstructions at the top and bottom of the ladder for access and egress;
 - 5.1.6 be free from defective or loose rungs; and
 - 5.1.7 be free and clear of debris and obstacles.